

Product Information



Date 13-10-2015

OROLAVICO: LAVA STONE - Bush Hammered

General Technical Characteristics

Natural Stone is sensitive to acids.

With a honed finish natural stone, avoid washing with acid based cleaner. This type of stone expresses a certain sensitivity to acids, highlighted by the classic reaction of carbon dioxide bubbles. This reaction affects the stone and could ruin the surface.

We recommend the use of alkaline or neutral products.

Pre-Treatment

Product
Equipment

Fila PW10 (Water Based)
Brush, Broom, Airless Spray Pump

Procedure

Thoroughly clean the back of the tile or slab removing the dust and debris. Apply the Fila PW10 on the back of the material with a flat brush or airless spray pump while avoiding stagnant application of the product. Let dry for about 12 hours. Make sure you rest the back sides, back to back. Avoiding contact with the front/top surface of the tiles.

Mix

1 Litre: 10 – 12 sq/m

Initial Cleaning

Product
Equipment
Procedure

Fila Cleaner diluted @ 1:20 per for medium - dirty floors.
Fila PS/87 diluted @ 1:5 for very dirty floors.
Large Areas - single disk floor cleaner with medium-hard bristles with a wet n dry vacuum cleaner action.
The initial cleaning is critical to remove debris and dirt. Washing must be performed with Fila Cleaner (diluted in twenty parts water) or Fila PS/87 (diluted in five parts water) using a single brush and vacuum cleaners. If you use the FILA PS/87 rinse thoroughly. This can be done by hand with broom and mop. In this case it is advisable to rinse the mop in the washing solution.

Mix

FilaCleaner: 1 Ltr per 50 sq/m
Fila PS/87: 1 Ltr per 20 sq/m

Stain Protection

Product	Fila W68 (water based)
Equipment	Brush, New Broom
Procedure	Apply an even coat of pure protective. The application of Fila W68 is possible in case of any slight moisture on the Natural Stone. Apply the second coat within 4 hours after the first coat.
Mix	1 Litre: 10 - 20 sq/m

General Maintenance

Product	Fila Cleaner
Equipment	Cloth or Mop. Commercial Cleaning Machine.
Procedure	For maintenance we recommend washing with diluted Fila Cleaner depending on the dirt. At high dilutions (1:200) rinsing is not required. Using the 1:200 dilution can be used with Commercial Cleaning Machines. Note: if possible, use warm water and wring out the cloth or mop and rinse often in detergent solution.
Mix	FilaCleaner: 1 Litre per 1500 sq/m @ 1:200
Note	To renew the layer of wax, you can periodically use a finishing wax diluted in water.

Fila Industrial Chemical Pty. Ltd.
Technical Laboratory

Instructions for use and procedures for implementing the recommended products are the result of specific verifications by the laboratory. However, there are factors beyond our control: surface condition prior to treatment, features/finishing material particularly rare or not as specified, environmental conditions, professionalism. We therefore recommend a preliminary test on the surface to be treated. The company always guarantees the quality of its products but is not liable for their misuse.